MDT 300-68 (MILL DUTY THRUSTER BRAKES)




INTRODUCTION

Thruster Brake is a device to retard the speed of moving machinery and to stop it accurately to the desired position. The breaking force is applied to the brake shoes by a pre-stressed compression spring. The shoes press on the rotating brake drum retarding its speed, and finally stopping it.

TECHNICAL DATA

ITEM	BRAKE	THRUSTER
MODEL	MDT - 300-68	ST- 870
DRUM DIA	300 mm	
BRAKE SHOE	Asbestos free/BA	
BRAKING TORQUE	90 Kg-m	
THRUST		68 Kg
STROKE		76 mm
OIL + CAPACITY		Transformer Oil 5 Litrs
RATED VOLTAGE		415V±10%,3PhAC,50Hz
CURRENT AT 415 V AC		0.7 Amps
POWER		200 Watt
INSULATION		F Class
INGRESS PROTECTION		IP-55 IS/IEC 60529(2001)
SURFACE TEMPERATURE		+50°C
WEIGHT	37 kg	34 kg
POWDER COATING	Colour RAL 7021	
OPTION		
LAF	Asbestos Free Liner	
LWI	Lining Wear Indicator	
OL	Open Brake Limit Switch	
MS	Manual Opening & Locking System	





SELECTION OF BRAKE SIZE


Electo-hydraulic thruster is a device which develops linear thrust (or force) required to operate the required mechanism. The input to the device is three phase supply.

The brake torque must be = >than motor full load as referred with drum. Formula as below:

T = Torque in Kgm =
$$\frac{716 \times Hp}{rpm}$$

T = Torque in Nm =
$$\frac{9552 \times Kw}{rpm}$$

Where Hp/Kw = motor output & rpm = Rev/minute



H. O. Unit -I: C-15/16, Nand Jyot Industrial Estate, Andheri-Kurla Road, Mumbai - 400072, Tel: (022) 42469700/730 E-mail: sales@socgroup.in Unit - II: Plot No. 4912, G. I. D. C., Phase IV, Vatva, Ahmedabad - 382445 Tel.: (079) 68169700/702/712 E-mail: enquiry2@socgroup.in

Visit us at : www.speedocontrols.com www.socremote.com www.socjoystick.com

